

# 5W-40 A3/B4 Pro S

## Description and Properties:

**5W-40 A3/B4 Pro S** is a high performance low friction oil, which is designed for gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines. It is blended from high quality hydrocracked base oils and selected additives. This makes for a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

**5W-40 A3/B4 Pro S** has following advantages to be pointed out

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C reduce fuel consumption.
- optimized high temperature viscosity and outstanding low friction properties lower oil-caused emissions.
- high wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

## Specification / Recommendations:

ACEA A3/B4	MB 229.5	PSA B71 2296
API SP	VW 502 00 / 505 00	Renault RN 0700 / 0710
BMW Longlife – 01	Porsche A 40	Lamborghini
MB 226.5	GM-LL-B-025	Maserati

## Typical Values:

5W-40 A3/B4 Pro S	Unit	Value	Method
Density at 15°C	kg/m <sup>3</sup>	853	DIN 51 757
Viscosity at 100°C	mm <sup>2</sup> /s	14,2	DIN 51 562
Viscosity Index		172	DIN ISO 2909
CCS at -30°C	mPa.s	6260	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,2	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.  
Further information available by MSDS.*

## Hengst SE

Nienkamp 55-85  
48147 Münster  
Germany  
Tel.: +49 251 20202-0

