

10W-40 SL Pro

Description and Properties:

Hengst 10W-40 SL Pro is a high performance crankcase oil to be used in passenger cars and light duty vehicles. It can be recommended for the consumption-optimised modern gasoline engine as well as for the high-output turbo charged diesel engine.

Hengst 10W-40 SL Pro is a motor oil, blended from mineral base oils and most modern additives. The excellent wear protection and the very good detergency/dispersancy, which efficiently control sludge build-up, have to be highlighted.

Specification / Recommendations:

API SL/CF

Typical Values:

10W-40 SL Pro	Unit	Value	Method
Density at 15°C	kg/m ³	861	DIN 51 757
Viscosity at 40°C	mm ² /s	96,6	DIN 51 562
Viscosity at 100°C	mm ² /s	14,8	DIN 51 562
Viscosity Index		158	DIN ISO 2909
CCS at -25°C	mPa.s	5380	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592
TBN	mg KOH/g	8,4	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85

48147 Münster

Germany

Tel.: +49 251 20202-0

