

10W-40 SL Pro

Description:

10W-40 SL Pro is a high performance crankcase oil to be used in passenger cars and light duty vehicles. It can be recommended for the consumption-optimised modern gasoline engine as well as for the high-output turbo charged diesel engine.

10W-40 SL Pro is a motor oil, blended from mineral base oils and most modern additives. The excellent wear protection and the very good detergency/dispersancy, which efficiently control sludge build-up, have to be highlighted.

Specification / Recommendations:

API SL/SJ/CF/
JASO MB

JASO MA

Typical Values:

10W-40 SL Pro	Unit	Value	Method
Density at 15°C	kg/m ³	856	DIN 51 757
Viscosity at 100°C		13.7	DIN 51 562
Viscosity Index	mPa.s	152	DIN ISO 2909
CCS at -25°C	°C	6000	DIN 51 377
Pourpoint	°C	-35	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	6.1	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst Filter Systems (Kunshan) Co.,Ltd
No.1858 North Jinshajiang Road 215300
Kunshan City,Jiangsu Province,China
Tel:+86(0)512 577 23700