

15W-40 E7 HD

Description:

15W-40 E7 HD is a high performance motor oil for modern heavily stressed diesel engines inclusive turbo charger. Because of its outstanding additive technology it also comes up to the most severe requirements of gasoline engines. This makes it being excellent provider for mixed-fleet.

Properties:

15W-40 E7 HD has following advantages to be pointed out

- excellent thermal/oxidative stability reduces sludge built-up und deposits
- allows maximum oil drain intervals by highest TBN-reserve.
- minimizes efficiently bore polishing.
- reduces oil aging, even at high temperatures.
- best seal and elastomer compatibility
- an all-seasons oil for mixed-fleet.

Specification / Recommendations:

ACEA E7-16	DETROIT DIESEL 93K215
CAT ECF-1/ECF-2	MACK EO-N/EO-M PLUS
GLOBAL DHD-1	MAN M 3275
CUMMINS CES 20077/20078	MTU Type 2.0
JASO DH-1	RENAULT RLD/RLD-2
VOLVO VDS-3	MB 228.3
	DEUTZ DQC-III-10

Typical Values:

15W-40 E7 HD	Unit	Value	Method
Density at 15°C	kg/m ³	855	DIN 51 757
Viscosity at 100°C		15.35	DIN 51 562
Viscosity Index	mPa.s	162	DIN ISO 2909
CCS at -20°C	°C	5323	DIN 51 377
Pourpoint	°C	-30	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	10.2	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst Filter Systems (Kunshan) Co.,Ltd
No.1858 North Jinshajiang Road 215300
Kunshan City,Jiangsu Province,China
Tel:+86(0)512 577 23700