

## 5W-30 C3 Pro

### Description:

**5W-30 C3 Pro** is a high performance fuel economy oil made from synthetic base oils. It is foreseen for the all-seasons use in passenger cars most modern gasoline- and diesel-engines, even with unit-injector. Due to its progressive conception it provides an extremely wide range of performances:

- Low sulphur-, phosphorus- and ash-content reduce poisoning of catalysators in gasoline engines and decrease the built-up of particles in the diesel particulate filter (DPF) and assist thus the environmental protection by lower pollution.
- High performance additivation assures optimal wear protection and best motor cleanliness..
- Excellent thermal oxidation stability reduces oil aging and allows longer drain intervals at maximum motor protection..
- Best low temperature properties enable unproblematic cold-start of the motor and contribute decisively to a longer operating life of the engine by rapid oil circulation

### Specification / Recommendations:

API SP  
MB 229.51 (deckt 229.31 ab)

ACEA C3  
MB 229.52

### Typical Values:

5W-30 C3 Pro	Unit	Value	Method
Density at 15°C	kg/m <sup>3</sup>	853	DIN 51 757
Viscosity at 100°C		12.04	DIN 51 562
Viscosity Index	mPa.s	167	DIN ISO 2909
CCS at -30°C	°C	5575	DIN 51 377
Pourpoint	°C	-40	DIN ISO 3016
Flashpoint	°C	220	DIN ISO 2592
TBN	mg KOH/g	6.76	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.  
Further information available by MSDS.*

**Hengst Filter Systems (Kunshan) Co.,Ltd**  
No.1858 North Jinshajiang Road 215300  
Kunshan City, Jiangsu Province, China  
Tel:+86(0)512 577 23700

