

## 5W-40 A3 / B4 Pro

### Description:

**5W-40 A3/B4 Pro** is a high performance low friction oil, which is designed for all gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines. It is blended from high quality synthetic base oils and selected additives. This makes for a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C.
- optimized high temperature viscosity to meet latest requirements leads to low oil-caused emissions.
- high wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

### Specification / Recommendations:

API SN  
PSA B71-2296  
Porsche A40  
VW 502.00/505.00

ACEA A3/B4  
Renault RN 0710/0700  
MB 229.3

### Typical Values:

| 5W-40 A3/B4 Pro    | Unit              | Value | Method       |
|--------------------|-------------------|-------|--------------|
| Density at 15°C    | kg/m <sup>3</sup> | 857   | DIN 51 757   |
| Viscosity at 100°C |                   | 14.02 | DIN 51 562   |
| Viscosity Index    | mPa.s             | 166   | DIN ISO 2909 |
| CCS at -30°C       | °C                | 6166  | DIN 51 377   |
| Pourpoint          | °C                | -42   | DIN ISO 3016 |
| Flashpoint         | °C                | 230   | DIN ISO 2592 |
| TBN                | mg KOH/g          | 10.4  | DIN ISO 3771 |

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.  
Further information available by MSDS.*

**Hengst Filter Systems (Kunshan) Co.,Ltd**  
No.1858 North Jinshajiang Road 215300  
Kunshan City, Jiangsu Province, China  
Tel:+86(0)512 577 23700

