

5W-40 C3 Pro

Description:

5W-40 C3 Pro is a high performance fuel economy oil made from synthetic base oils. It is foreseen for the all-seasons use in passenger cars most modern gasoline- and diesel-engines, even with unit-injector. Due to its progressive conception it provides an extremely wide range of performances:

- Low sulphur-, phosphorus- and ash-content reduce poisoning of catalysators in gasoline engines and decrease the built-up of particles in the diesel particulate filter (DPF) and assist thus the environmental protection by lower pollution.
- High performance additivation assures optimal wear protection and best motor cleanliness..
- Excellent thermal oxidation stability reduces oil aging and allows longer drain intervals at maximum motor protection..
- Best low temperature properties enable unproblematic cold-start of the motor and contribute decisively to a longer operating life of the engine by rapid oil circulation

Specification / Recommendations:

API SP
MB 229.51 (deckt 229.31 ab)

ACEA C3

Typical Values:

5W-40 C3 Pro	Unit	Value	Method
Density at 15°C	kg/m ³	854	DIN 51 757
Viscosity at 100°C		13.96	DIN 51 562
Viscosity Index	mPa.s	166	DIN ISO 2909
CCS at -30°C	°C	6205	DIN 51 377
Pourpoint	°C	-40	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592
TBN	mg KOH/g	6.76	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst Filter Systems (Kunshan) Co.,Ltd
No.1858 North Jinshajiang Road 215300
Kunshan City, Jiangsu Province, China
Tel:+86(0)512 577 23700