MATERIAL SAFETY DATA SHEET

Note:Read and understand Material Safety Data Sheet before handling or disposing of product.

Issued date:March 10,2023

MSDS No.HENGST

SECTION1.CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY IDENTIFICATION

HENGST Filter System (Kunshan) CO., LTD

No.1858 North Jinshajiang Road215300 Kunshan City, Jiangsu **Province China** EMERGENCY TELEPHONE NUMBER: +86(0)512 577 23700 +86(0)512 577 23700 **TELEPHONE NUMBER FOR INFORMATION:** FAX NUMBER FOR INFORMATION: +86(0)512 577 23702 **PRODUCT NAME:** 5W-40 C3 Pro PRODUCT USE: **ENGINE OIL** SECTION2.COMPOSITION/INFORMATION ON INGREDIENTS COMPOSITION Amount(%) Components Limit Highly refined petroleum oil 5 mg/m³ >74.6 TWA-OSHA(MineralOilMist#1) <25.4 TWA-ACGIH(MineralOilMist#1) 5mg/m^3

Additives

Additives for ENGINE OIL

Hazardous information

1 Highly refined petroleum oil, by definition, is considered hazardous according to OSHA. Because it carries the Threshold limit value(TLV) for mineral oil mist.

SECTION3.HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Warning statement:

Caution! Prolonged or repeated contact with skin may cause irritation in some cases. Precautionary Measures:

| | Avoid breathing vapor and mist. Keep container closed. | | |
|--------------------------|--|--|--|
| | Avoid contact with eyes, skin, and clothing. | | |
| | Wash thoroughly after handling. Keep away from heat. | | |
| Potential health effect: | | | |
| Eyes: | May cause minor irritation. | | |
| Skin: | May cause minimal skin irritation. | | |
| Inhalation: | Vapor or mist, in excess of permissible concentrations, or in unusually high concentrations generated froms praying, heating the material, or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness. | | |
| Ingestion: | May cause abdominal discomfort, nausea, or diarrhea. | | |
| Sensitizationprop | erties: Unknown | | |
| ChronicProperties | If prolonged exposure occurs, nausea, headache, diarrhea, and physical discomfort. | | |

Other remarks: None

SECTION4.FIRST AID MEASURES

| Eyes: | Flush immediately with water for at least1 5 minutes. Get immediate medical attention. |
|------------------|--|
| Skin: | Wash with soap and water. Get medical attention if irritation develops. |
| | Launder contaminated clothing beforere use. |
| Inhalation: | Remove exposed person to fresh air if adverse effects are observed. |
| Ingestion: | Do not make person vomit unless directed to do so by medical personnel. |
| Notetophysician: | Treat symptomatically. |

SECTION5.FIRE FIGHTING MEASURES

| Flash point(Typical),℃ | >215(COC) |
|-----------------------------------|--|
| Auto ignition tempt., °C | Not Determined. |
| Flammability limits: | Not Determined. |
| Extinguishing media: | CO ₂ , drychemical, orfoam. |
| Special fire fighting procedures: | Recommend wearing self-contained breathing apparatus. Water may cause splattering. Material will float on water. |
| Unusual fire&explosion hazards: | Toxic fumes, gases or vapors may evolve on burning. |
| Autoignition temperature: | Not determined. |
| Explosion data: | Material does not have explosive properties. |

SECTION6.ACCIDENTAL RELEASE MEASURES

Procedures in Case of Accidental Release, Breakage or Leakage:

Stop the source of the leak or release. Clean up releases as soon as possible. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.

SECTION7.HANDLING AND STORAGE

Do not weld, heat or drill container. Replace cap or bung. Emptied container still contains hazardous material which may ignite with explosive violence if heated sufficiently.

Minimum feasible handling temperatures should be maintained.

Periods of exposure to high temperatures should be minimized.

Water contamination should be avoided.

CAUTION: Do not use pressure to empty drum or drum may rupture with explosive force.

SECTION 8.EXPOSURE CONTROLS/PERSONAL PROTECTION

| Eye Protection: | Chemical type goggles or face shield optional. | |
|------------------------------------|--|--|
| Skin Protection: | Avoid prolonged or frequently repeated skin contact by wearing impervious protective | |
| | Clothing including gloves. | |
| Respiratory Protection: | Wear a breathing mask. | |
| Ventilation: | No special ventilation is usually necessary. However, if operating conditions create | |
| | High air borne concentrations of this material, special ventilation may be needed. | |
| Other clothing and Equipment: | No special clothing or equipment is usually necessary, | |
| Work practices, hygienic practices | s: No information is available. | |
| Other handling and storage requir | rements: No information is available. | |
| | | |

Protective measures during maintenance of contaminated equipment: No Data Available.

SECTION9.PHYSICAL AND CHEMICAL PROPERTIES

| Odor | | Slight odor |
|---------------|-------------------------|--------------------|
| Appearance | | Yellow liquid |
| Boiling point | S | No Data Available |
| Solubility | | Insoluble in water |
| Density | $@20^{\circ}C,g/cm^{3}$ | 0.853 |
| Pour point | °C | <-35 |

SECTION 10. STABILITY AND REACTIVITY

| Stability: | Stable | |
|------------------------------------|--|--|
| Conditions to Avoid: | See the Handling and storage section for further details. | |
| Incompatibility(materialstoavoid): | erialstoavoid): Acids. Oxidizing agents. Halogens and halogenated compounds. | |
| Hazardous Polymerization: | Will not occur | |
| Thermal decomposition: | Smoke, carbon monoxide, aldehydes and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released. Under combustion conditions, oxides of the following elements will be formed: Calcium, Sulfur, Zinc. | |
| | | |

SECTION11.TOXICOLOGICALINFORMATION

| Acute Oral: | No Data Available: | Believed to be greater than 5g/kg(rat) Practically non-toxic | |
|---------------------------|--------------------|--|--------|
| Dermal: | No Data Available: | Believed to be greater than 3 g/kg(rabbit) Practicallynon- toxic | |
| Carcinogen: (Baseoil) | OSHA: EU: | This material is listed as Group 3 by IARC. The classification as a carcinogen need not a | ipply. |

SECTION 12. ECOLOGICAL INFORMATION

 Biodegradation:
 No Data Available

 Environmentalfate:
 This material is not expected to present any environmental problems other than those associated with oil spills.

SECTION13.DISPOSALCONSIDERATIONS

WasteDisposalMethod:

Place contaminated materials indisposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental or health authorities for approved disposal of this material.

SECTION14.TRANSPORTINFORMATION

The description shown may not apply to all shipping situations.

| DOT | Proper Shipping Name: | Not applicable. |
|-----------|-----------------------|-----------------|
| IMDG | Proper Shipping Name: | Not applicable. |
| ICAO | Proper Shipping Name: | Not applicable. |
| TDG | Proper Shipping Name: | Not applicable. |
| NFPA | Proper name: | Class1. |
| UN umber: | • | Not applicable. |

SECTION15.REGULATIONINFORMATION

The U. S. TSCA inventory: The EC EINECS inventory: The CANADA DSL inventory: The AUSTRALIA AICS inventory: The KOREA TCCL inventory: The PHILIPPINE PICCS inventory: All components of this material are on the US TSCA inventory. All components of this material are on the EC EINECS inventory. All components of this material are on the DSL inventory. May require notification before sale in AUSTRALIA. May require notification before sale in KOREA. No Data Available.

SECTION16.OTHERINFORMATION

None

References:

1 . Handbook of Toxic and Hazardous Chemicals and Carcinogens($2^{\mbox{ nd}}$ ed.)

2. Registry of Toxic Effects of Chemical Substances(NIOSH, 1983)

Material safety data sheets are provided as reference information on the safe handing of hazardous or harmful materials to companies using such materials. When referring to this data sheet, companies should remember that they must take responsibility for implementing the proper measures for their own particular situations. This data sheet is not aguarantee of safety.